

TR:普通直通型, TRR : 90° 转角型

Data 性能参数		Type Stage	TR40	TR60	TR90	TR115	TR140	TR160	
		型号段数	TRR40	TRR60	TRR90	TRR115	TRR140	TRR160	
Nominal output Torque T_{2N}	Nm	1-stage 1段	3:1	17	28	85	115	210	400
			4:1	20	44	120	260	450	800
			5:1	18	40	110	230	400	700
			6:1	-	25	75	200	260	650
			8:1	6	18	50	120	210	450
			10:1	-	15	32	100	130	305
		2-stage 2段	9:1	17	28	85	125	210	400
			12:1	20	44	120	260	450	800
			15:1	18	40	110	230	400	700
			16:1	20	44	120	260	450	800
			20:1	20	44	120	260	450	800
			25:1	18	40	110	230	400	700
			30:1	-	40	110	230	260	700
			32:1	20	44	120	260	450	800
			36:1	-	25	75	200	260	650
			40:1	20	40	110	230	400	700
			48:1	-	25	75	200	260	650
			50:1	18	40	110	230	300	700
			64:1	6	18	50	120	210	450
			100:1	-	15	32	100	130	305
		3-stage 3段	60:1	20	44	120	260	450	800
			64:1	20	44	120	260	450	800
			75:1	18	40	110	230	400	700
			80:1	20	44	120	260	450	800
			90:1	18	40	110	230	400	700
			100:1	20	44	120	260	450	800
			120:1	20	40	120	260	450	800
			125:1	18	40	110	230	400	700
			150:1	18	40	110	230	400	700
			160:1	20	44	120	120	450	800
			180:1	18	40	110	110	400	700
			200:1	18	40	110	230	400	700
			240:1	18	40	110	230	400	700
			256:1	20	44	120	260	450	800
			320:1	18	40	110	230	400	700
			384:1	16	25	75	200	260	650
			512:1	6	18	50	120	210	450
			600:1	-	25	75	200	260	650
		800:1	-	18	50	120	210	450	
		1,000:1	-	15	32	100	130	400	